

9" ADVANCED INFOTAINMENT SYSTEM

INTEGRATED HEAD UNIT UPGRADE

to suit **LANDCRUISER 200 SERIES SAHARA (2012-2015)**



AMUTO52 INSTALLATION MANUAL

CONTENTS

Tools Required	2
Product Overview	2
Inclusions	2
Pre-installation Checks	2
Connection Wiring Diagram	3
Wiring Diagram	4
Dash Disassembly	5 - 14
DAB+ Antenna	15
Microphone Installation	15
Unit Installation	16-17
Dash Reassembly	18-19
Installation Checklist	20
Technical Assistance	21

Tools Required


Use the following tools to make dismantling the dash and the installation of the new kit easier.

NOTE: Do not use power tools, only use the tools recommended below, and do not over tighten screws as they may damage other components. Also take care in removing trim panels as over time they may have become brittle.


1. Plastic panel remover (pry tool)



2. Phillips Head Screwdriver



3. 10mm socket, extension, and ratchet



Product Overview

The Aerpro AMUTO51B is a head unit replacement kit to suit the Toyota Landcruiser 200 Series Sahara 2010-2011 models. These kits are Australian designed and engineered to replace the original Toyota head unit and retain the vehicles original functions* while adding features such as Apple CarPlay, Android Auto, larger 9" High Definition display, DAB+ & Dual USB inputs.

Inclusions



- Infotainment unit
- Infotainment monitor with physical buttons
- Mounting brackets and screws
- Main harness
- LVDS cable
- GPS Adaptor
- DAB+ Antenna
- External Microphone with Clip-on bracket
- Stick-on Microphone bracket
- Audio Visual (AV) harness
- MOST Adaptor

Pre-installation checks

Prior to disassembling the dash and removing the original head unit perform the following checks to determine their functionality:


- | | |
|--|--|
| ☐ Steering wheel controls | ☐ Factory reset system Settings |
| ☐ Climate controls | ☐ Factory vehicle settings |
| ☐ Hazard light switch | ☐ Audio output and adjustment |
| ☐ AM / FM | ☐ Factory Camera |
| ☐ Factory USB Port | |

Connection wiring diagram






①	Segment Connector
②	LVDS Connector / Cable
③	Button Display Connector
④	MOST Amplifier Connector
⑤	Camera Connector
⑥	Amplifier Stereo Connector
⑦	Multiplex Connector (28 pin)
⑧	USB 1: CP/AA
⑨	USB 2: Media
⑩	AM/FM Antenna
⑪	GPS Antenna
⑫	AV Harness / AV Connector
⑬	Multiplex Connector (20 pin)
⑭	DAB+ Antenna
⑮	Microphone
⑯	USB Panel Adaptor

Wiring diagram



12 AV Harness 24 Pin




Dash disassembly

Remove the panel which is located by the left knee of the driver by pulling it firmly toward yourself. Place this panel aside.



Remove the panel which is located by the left knee of the driver by pulling it firmly toward yourself. Place this panel aside.



Dash disassembly continued...

Remove the panel with the engine start / stop button by pulling it firmly on an slight angle toward yourself as shown



Disconnect the harness leading to the engine start / stop button and the 4WD mode selector switch. Place this panel aside.




Dash disassembly continued...

Repeat the process on the opposite side, remove the panel located by the right knee of the passenger by pulling it firmly toward yourself. Place this panel aside.



Remove the 10mm screw and retaining clip indicated below.



Dash disassembly continued...

Repeat the process for the opposite panel to the Start/Stop button. See page 6.



Remove the gear shift knob by unscrewing




Dash disassembly continued...

Remove the accessory socket panel below the stereo controls by pulling firmly toward the rear of the vehicle.



Disconnect the harnesses leading to the accessory socket to remove this panel. Place this panel aside.



Dash disassembly continued...

Remove the speaker grille at the top of the dash by gently using a plastic pry tool along the front edge and both sides to release the clips.



With the speaker grille unclipped, disconnect the light sensor harness to remove it completely. Place this panel aside.



Dash disassembly continued...

Remove the 2x 10mm screws from under the grille holding the top of the display as shown below. Place these aside, they will be reused.



Gently pull the factory display toward you slightly (not removing it yet) to help pop the vent clips so you don't have to use a pry tool against the dash.



Dash disassembly cont

Remove both vents and unplug the harnesses for the temperature control buttons. Place them aside.




Remove the 2x 10mm bolts from behind the vents either side of the display as indicated below. These will be reused. Remove the display by pulling in the center on both sides.



Dash disassembly cont

Place a soft cloth under the display to rest it on making it easier to unplug all of the harnesses and remove the display. The display will not be reused.



Remove the 2x 10mm screws either side of the head unit circled in red below. Pull the head unit toward you to remove.



Dash disassembly cont

Unplug the 2x harnesses and remove the head unit. The original head unit will not be reused.



Microphone and DAB antenna install

Remove the passenger A pillar grab handle and panel to run the Microphone and DAB+ antenna.




Unit installation

Install the brackets supplied in the kit to the sides of the new head unit.



Connect the necessary harnesses to the new head unit.



Unit installation

Route all of the harnesses to the top section of the dash where the new head unit will be installed.



Install the new head unit and secure it using the original mounting locations and screws placed aside. Be sure to route the 3x cables (segment display connector, LVDS, and button display connector) required for the new display out the bottom of the new head unit.




Dash Reassembly

Install the supplied pocket (or optional switch panel) in the place of the factory head unit



Connect the new display to the 3x harnesses routed out from under the new head unit.



Dash Reassembly

Line up the clips of the new display and push it evenly and firmly into place.



The dash can now be reassembled in the reverse order of the steps taken on pages 5 to 14.



Testing the new unit

Perform the following checks to determine their functionality:

- ☐ AM / FM / DAB+
- ☐ Apple CarPlay
- ☐ Android Auto
- ☐ Audio output and adjustment*
- ☐ Bluetooth microphone
- ☐ Steering wheel controls
 - ☐ Volume up / down
 - ☐ Track change next/ previous
 - ☐ Mode
 - ☐ Voice control
 - ☐ Phone buttons answer / hang up
- ☐ USB ports
- ☐ 360 degree camera
 - ☐ View change button
- ☐ Climate controls
 - ☐ AC function
 - ☐ Temperature up / down
 - ☐ Vent location
 - ☐ Air re-circulation
 - ☐ Fan speed
 - ☐ 4-zone setting
 - ☐ Demisters front / rear
 - ☐ Outside temperature
- ☐ Hazard light switch
- ☐ Factory vehicle settings
 - ☐ Sound settings (Change sound settings to update vehicle info)
- ☐ Second camera (if fitted)

**** IMPORTANT INFORMATION****

You may need to increase Factory Amplifier volume in the Sound Settings if volume is low

Technical assistance

If you need assistance setting up or using your Aerpro product now or in the future, call Aerpro Support. Australia

TEL: 03 – 8587 8898

FAX: 03 – 8587 8866 Mon-Fri 9am – 5pm AEST or EMAIL: service@tdj.com.au

If you would like to download a digital copy of this manual, or other Aerpro manuals/software, please visit the Aerpro.com website and search for the product model number for more information, accessories and products.

This manual is considered correct at time of printing but is subject to change. For latest manuals and updates refer to the website.

Copyright © 2026 by TDJ Australia

All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, copying or other electronic or mechanical methods, without the prior written permission of the author.

AERPRO.COM



R-NZ



Apple CarPlay is a trademark of Apple Inc. Use of the Apple CarPlay logo means that a vehicle user interface meets Apple performance standards. Apple is not responsible for the operation of this vehicle or its compliance with safety and regulatory standards. Please note that the use of this product with iPhone, iPod, or iPad may affect wireless performance. Apple CarPlay requires a compatible device, mobile data, network reception & GPS signal. Mobile usage at user's cost. Please visit apple.com/au/ios/carplay/ for device compatibility.

Apple, iPhone, iPod, iPad and Siri are trademarks of Apple Inc., registered in the U.S. and other countries. Apple CarPlay is a trademark of Apple Inc.

Android, Android Auto, Google Assistant, and Google are trademarks of Google Inc.

Availability of Android Auto may vary depending upon your country and phone model. To wirelessly use Android Auto on your car display, you need a compatible Android smartphone with an active data plan. You can check which smartphones are compatible android.com/auto.

While this product is compatible for use with Bluetooth, it is not made or endorsed by Bluetooth SIG inc.

DAB+ and all related marks and logos are trademarks of WorldDAB. All rights reserved.

Other trademarks and trade names are those of their respective owners.

Some vehicle features may not be retained, or may function differently. For more information visit aerpro.com. iPhones, Android smartphones or any other accessories shown or listed are not supplied and must be purchased separately.

Design and specifications are subject to change without notice.