

# CHSK4C

# Steering Wheel Control Interface for select Skoda vehicles





















# **Vehicle Application**

Skoda Octavia (1Z) 2008 - 2013 Skoda Superb 2008 - 2013 Skoda Fabia (5J) 2013 - 2014 Skoda Rapid 2012 - 2015 Skoda Yeti (5L) 2009 - 2014

## **Key Features**

- · Retains Steering Wheel Controls (if equipped)
  - Retains OEM Phone Buttons(if equipped)
- Provides Speed Pulse, Park Brake, Reverse Gear and Illumination Feeds



#### **ABOUT THIS PRODUCT**

#### CHSK4C

CAN-BusSteeringWheel Control Interface for Skoda vehicleswith Quadlock connector.

#### WIRING COLOUR CODES

Purple	Right Rear Speaker +	Yellow	Permanent 12V
Purple/Black	Right Rear Speaker -	Black	Ground
Green	Left Rear Speaker +	Red	Ignition 12V
Green/Black	Left Rear Speaker -	Orange	Illumination
Grey	Right Front Speaker +	Pink	Speed Pulse
Grey/Black	Right Front Speaker -	Green	Park Brake
White	Left Front Speaker +	Purple/White	ReverseGear
White/Black	Left Front Speaker -		

#### PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge isnecessary for installation. Theplace of installationmust be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. Aerpro cannot be held responsible for the installation of this product.

#### TECHNICAL SUPPORT

If you need assistance setting up or using your Aerpro product now or in the future, call Aerpro Support Australia

TEL: 03 – 8587 8898 FAX: 03 – 8587 8866 Mon-Fri 9am – 5pm AEST. If you would like to download a digital copy of this manual, or other Aerpro manuals/software, please visit the http://aerpro.com website.

#### **FITTING GUIDE**

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB:Thismay be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: Thisstep must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISOharnessto the female power/speaker ISOharnessfrom the aftermarket head unit. Foraftermarket head unitswithout an ISO connector, please refer to "Wiring Colour Codes" on Pg.2.





#### **FITTING GUIDE**

6. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Testhead unit for correct operation.

### STEERINGWHEELCONTROL FUNCTIONALITY

Original Button	Function	
VOL +	Volume +	
VOL -	Volume -	
Right Arrow	Track +	
Left Arrow	Track -	
Mute Icon	Mute	
Phone Button	Pick Up (Short Press)	
Phone Button	Hang Up (Long Press)	